


Performance characteristics:

- RF/LO band: 6GHz-18GHz
- IF band: DC-6GHz
- Frequency conversion loss: 7dB
- RF-IF Isolation: 15dB
- LO-IF isolation: 45dB
- LO-RF isolation: 48dB
- Local oscillator power: 20dBm
- Package size: :3*3 QFN 12L

Functional block diagram



Product Description:

CW-MX141SP3B is a GaAs MMIC passive double balanced mixer, with RF/LO frequency covering 6-18GHz and IF frequency covering DC-6GHz respectively, conversion loss less than 8dB, RF-IF isolation greater than 11dB, LO-IF isolation greater than 41dB, LO-RF isolation greater than 45dB, and typical LO input power of 20dBm.

Electrical parameters: (TA=25 °C, IF=0. 1GHz, LO=20dBm)


Indicators	Minimum value	Typical value	Maximum value	Unit
Radio frequency	6-18			GHz
Local oscillator frequency	6-18			GHz
Intermediate frequency	DC-6			GHz
Frequency conversion loss	6.5	7	8	dB
RF-IF isolation	11	15	22	dB
LO-IF isolation	41	45	51	dB
LO-RF isolation	45	48	50	dB
P1dB (input)	11	12	13	dBm

Use limit parameters: (Exceeding any of the above maximum limits may cause permanent damage.)


RF/IF power	20 dBm
Local oscillator power	27 dBm
Storage temperature	-65 °C ~ 150 °C
Operating temperature	-55 °C ~ 125 °C

Typical curve:


Frequency conversion loss curve @
LO=20dBm, IF frequency 0.1 GHz




Isolation @ LO=20dBm, IF 0.1 GHz




Frequency conversion loss @
IF frequency 0.1 GHz




IF bandwidth @ LO=18GHz,
LO=20dBm




RF return loss




IF return loss



Enter P-1 @ LO=17dBm




Enter IP3 @ LO=17dBm




Absolute maximum rating

RF/IF input power	28dBm
LO input power	28dBm
Storage temperature	-65 °C ~ + 150 °C
Operating temperature	-40 °C ~ + 85 °C
ESD_HBM	Class 1A

Typical application



Package outline dimensions




- Description:
1. Unit: mm
 2. Lead frame material: copper alloy
 3. Package surface warpage: $\leq 0.05\text{mm}$
 4. Please connect all ground pins to PCB RF ground

Symbol	MIN	NOM	MAX
A	0.70	0.75	0.80
A1	0.00	0.02	0.05
A2	0.20Ref		
b	0.17	0.22	0.27
D	2.90	3.00	3.10
D2	1.05	1.15	1.25
e	0.50BSC		
Ne	1.00BSC		
Nd	1.00BSC		
E	2.90	3.00	3.10
E2	1.05	1.15	1.25
K	0.20	---	---
L	0.40	0.50	0.60
aaa	0.08		

Absolute maximum rating

Pin number	Functional symbol	Functional description
1;3;4;6;7;9	GND	RF ground, the exposed paddle at the bottom of the package is also RF & DC RF ground.
2	LO	Local Oscillator Port, AC Coupled Outside Matched 50 Ω , With Isolation Capacitor
5	IF	IF Port, DC Coupled Outside Matched 50 Ω No Isolation Capacitors
8	RF	RF port, AC coupled outer matching 50 Ω , with isolation capacitors.
10-12	NC	No internal connections

IF port definition



LO port definition



RF Port Definition

